

## Centrifuge Sheet



# Polyurethane Products

Centrifuge sheet is available in a shore hardness range of 45 Shore 'A' to 95 Shore 'A'.

It is available in thicknesses ranging from 1.0mm to 13mm. Standard sheet lengths are 3715mm nominally, with the widths being 686mm.

We offer a large range of colour options, for more details on these please contact the sales department.

Thickness (mm)	Weight (kg)
1.0	2.9
1.5	4.4
1.6	4.8
2.0	5.8
3.0	8.7
4.0	11.6
5.0	14.5
6.0	17.4
7.0	20.3
8.0	23.2
9.0	26.1
10.0	29.1
11.0	32.0
12.0	34.9
13.0	37.8

Thickness (ins)	Metric Equivalent (mm)	Weight (kg)
1/16	1.5875	4.6
1/8	3.1750	9.2
3/16	4.7625	13.8
1/4	6.3500	18.4
5/16	7.9375	23.1
3/8	9.52500	27.7
7/16	11.1100	32.3
1/2	12.7000	36.9

# Polyurethane Products

## Press Break Film



Press break film is available in a shore hardness range of 80 Shore 'A' to 95 Shore 'A'.

It is available in thicknesses ranging from 0.5mm to 1.5mm. Standard sheet dimensions are 3600mm (Long) x 150mm (Wide) nominally.

We offer a large range of colour options, for more details on these please contact the sales department.

Thickness (mm)
0.5
0.6
0.7
0.8
0.9
1.0
1.1
1.2
1.3
1.4
1.5

# Polyurethane Products

## Polyurethane Hot Table Cast Sheet

Polyurethane hot table cast sheets are available in a shore hardness range of 45 Shore 'A' to 60 Shore 'D'. It is also available in Vulkollan®.

They are available in sizes up to 2700 x 1200mm x 12mm thick.

The standard colours available are; red, black, ochre, natural, green, blue, yellow and orange. Although some of these may be subject to additional charges dependant on the grading of the polyurethane.

## Polyurethane Square Bar

Polyurethane square bars are available in a shore hardness range of 45 Shore 'A' to 60 Shore 'D'. It is also available in Vulkollan®.

They are available in sizes up to 500mm x 500mm x 100mm high.

The standard colours available are; red, black, ochre, natural, green, blue, yellow and orange. Although some of these may be subject to additional charges dependant on the grading of the polyurethane.

We are also able to offer these in standard sizes. The specifications are listed below.

Part Number	Short Description	Dimensions (mm)				
		W	x	T	x	L
PUSQB001	1 x 24" Bar	25.4	x	25.4	x	610
PUSQB002	1.5 x 24" Bar	38.1	x	38.1	x	610
PUSQB003	2 x 24" Bar	50.8	x	50.8	x	610
PUSQB004	60 x 610mm Bar	60.0	x	60.0	x	610
PUSQB005	3 x 24" Bar	76.2	x	76.2	x	610
PUSQB006	35 x 610mm Bar	35.0	x	35.0	x	610

## Polyurethane Slab

Polyurethane slabs are available in a shore hardness range of 45 Shore 'A' to 60 Shore 'D'. It is also available in Vulkollan®.

They are available in sizes up to 1500mm x 1200mm x 60mm thick, with a maximum weight of 60kg.

The standard colours available are; red, black, ochre, natural, green, blue, yellow and orange. Although some of these may be subject to additional charges dependant on the grading of the polyurethane.

Vulkollan® is made under licence from Bayer AG